

## TECHNICAL DATA

MODEL	FUX-C
<b>CAPACITY</b>	
Boxes and containers positioned across conveyor, trays and baking sheets up to 600 x 400 x 400 mm	150   300 /h
<b>FRESH WATER CONSUMPTION</b>	240 l/h
<b>TANK VOLUME</b>	125 l
<b>TOTAL LOADING</b> (without blow drying)	26.9 kW*
<b>HEAT OUTPUT</b>	
Wash tank	12   18 kW
Heat recovery rinse booster / hot water connection(max. 60°C)	12 kW
Rinse booster for cold water connection	21 kW
<b>WASH PUMP CAPACITY</b>	2.2   4.0 kW
<b>BLOW DRYING B</b> (optional)	2 x 2.7 kW
Fuse in A	3 x 50
Nominal voltage in V / Hz /N-PE	400 /50 /3
Noise level	76 db (A)
<b>DIMENSIONS</b>	
Width	992 mm
Length	3,000 mm
Height	1,474 mm
Loading width	612 mm
Loading height	440 mm
Length of blow drying unit	600 mm
<b>FEATURES</b>	
Container turning device	○
Heat recovery	○
Temperature display	●
Rinse pump	●

● Included      ○ Optional

\* With warm water connection 60 °C or heat recovery